


# LOAD TABLES | HEAVY DUTY, IMPERIAL

## LOAD TABLES - WIDE-GAP



**Grating Type:** 30HW4  
**Design Code:** NAAMM MBG 534-19  
**Material:** ASTM A1011CS Grade 36  
**Surface:** Smooth

U = Safe Uniform Load (lbs/ft<sup>2</sup>)  
D<sub>u</sub> = Deflection Due to Safe Uniform Load (in)  
C = Safe Concentrated Load (lbs/ft of grating width)  
D<sub>c</sub> = Deflection Due to Safe Concentrated Load (in)  
Allowable Extreme Fiber Stress = 20 ksi


Bearing Bar Size (inches)	Approx. Weight (lbs/ft <sup>2</sup> )	Ped. Span (inches)	Load / Deflection	Span (ft-in)												Section Properties			
				1' - 0"	1' - 6"	2' - 0"	2' - 6"	3' - 0"	3' - 6"	4' - 0"	4' - 6"	5' - 0"	5' - 6"	6' - 0"	6' - 6"	7' - 0"	7' - 6"	8' - 0"	
S <sub>x</sub> (in <sup>3</sup> )/ft	I <sub>x</sub> (in <sup>4</sup> )/ft																		
1" x 1/4"	6.77	55	U D <sub>u</sub> C D <sub>c</sub>	3,556	1,580	889	569	395	290	222	176	142						0.267	
				0.02	0.05	0.08	0.13	0.19	0.25	0.33	0.42	0.52						0.133	
				1,778	1,185	889	711	593	508	444	395	356							
				0.02	0.04	0.07	0.10	0.15	0.20	0.26	0.34	0.41	0.41						
1 1/4" x 1/4"	8.13	65	U D <sub>u</sub> C D <sub>c</sub>	5,556	2,469	1,389	889	617	454	347	274	222	184					0.417	
				0.02	0.04	0.07	0.10	0.15	0.20	0.26	0.34	0.41	0.50					0.260	
				2,778	1,852	1,389	1,111	926	794	694	617	556	505						
				0.01	0.03	0.05	0.08	0.12	0.16	0.21	0.27	0.33	0.40	0.40					
1 1/2" x 1/4"	9.49	74	U D <sub>u</sub> C D <sub>c</sub>	8,000	3,556	2,000	1,280	889	653	500	395	320	264	222	189			0.600	
				0.01	0.03	0.06	0.09	0.12	0.17	0.22	0.28	0.34	0.42	0.50	0.58			0.450	
				4,000	2,667	2,000	1,600	1,333	1,143	1,000	889	800	727	667	615				
				0.01	0.02	0.04	0.07	0.10	0.14	0.18	0.22	0.33	0.40	0.47	0.47				
1 1/2" x 3/8"	13.74	82	U D <sub>u</sub> C D <sub>c</sub>	12,000	5,333	3,000	1,920	1,333	980	750	593	480	397	333	284	245		0.900	
				0.01	0.03	0.06	0.09	0.12	0.17	0.22	0.28	0.34	0.42	0.50	0.58	0.68		0.675	
				6,000	4,000	3,000	2,400	2,000	1,714	1,500	1,333	1,200	1,091	1,000	923	857			
				0.01	0.02	0.04	0.07	0.10	0.14	0.18	0.22	0.33	0.40	0.47	0.54				
2" x 1/4"	12.21	92	U D <sub>u</sub> C D <sub>c</sub>	14,222	6,321	3,556	2,276	1,580	1,161	889	702	569	470	395	337	290	253	222	1.067
				0.01	0.02	0.04	0.06	0.09	0.13	0.17	0.21	0.26	0.31	0.37	0.44	0.51	0.58	0.66	1.067
				7,111	4,741	3,556	2,844	2,370	2,032	1,778	1,580	1,422	1,293	1,185	1,094	1,016	948	889	
				0.01	0.02	0.03	0.05	0.07	0.10	0.13	0.17	0.21	0.25	0.30	0.35	0.41	0.47	0.53	
2 1/2" x 1/4"	14.93	109	U D <sub>u</sub> C D <sub>c</sub>	22,222	9,877	5,556	3,556	2,469	1,814	1,389	1,097	889	735	617	526	454	395	347	1.667
				0.01	0.02	0.03	0.05	0.07	0.10	0.13	0.17	0.21	0.25	0.30	0.35	0.41	0.47	0.53	2.083
				11,111	7,407	5,556	4,444	3,704	3,175	2,778	2,469	2,222	2,020	1,852	1,709	1,587	1,481	1,389	
				0.01	0.01	0.03	0.04	0.06	0.08	0.11	0.13	0.17	0.20	0.24	0.28	0.32	0.37	0.42	
3" x 1/4"	17.65	125	U D <sub>u</sub> C D <sub>c</sub>	32,000	14,222	8,000	5,120	3,556	2,612	2,000	1,580	1,280	1,058	889	757	653	569	500	2.400
				0.01	0.02	0.03	0.04	0.06	0.08	0.11	0.14	0.17	0.21	0.25	0.29	0.34	0.39	0.44	3.600
				16,000	10,667	8,000	6,400	5,333	4,571	4,000	3,556	3,200	2,909	2,667	2,462	2,286	2,133	2,000	
				0.01	0.01	0.02	0.03	0.05	0.07	0.09	0.11	0.14	0.17	0.20	0.23	0.27	0.31	0.35	
3" x 3/8"	26.53	138	U D <sub>u</sub> C D <sub>c</sub>	48,000	21,333	12,000	7,680	5,333	3,918	3,000	2,370	1,920	1,587	1,333	1,136	980	853	750	3.600
				0.01	0.02	0.03	0.04	0.06	0.08	0.11	0.14	0.17	0.21	0.25	0.29	0.34	0.39	0.44	5.400
				24,000	16,000	12,000	9,600	8,000	6,857	6,000	5,333	4,800	4,364	4,000	3,692	3,429	3,200	3,000	
				0.01	0.01	0.02	0.03	0.05	0.07	0.09	0.11	0.14	0.17	0.20	0.23	0.27	0.31	0.35	

# of Bars	2	3	4	5	6	7	8	9	10	11
1/4" Bars	2-1/8	4	5-7/8	7-3/4	9-5/8	11-1/2	13-3/8	15-1/4	17-1/8	

# LOAD TABLES | HEAVY DUTY, IMPERIAL

## LOAD TABLES - WIDE-GAP

**Grating Type:** 30HW4  
**Design Code:** NAAMM MBG 534-19  
**Material:** ASTM A1011CS Grade 36  
**Surface:** Serrated



U = Safe Uniform Load (lbs/ft<sup>2</sup>)  
D<sub>u</sub> = Deflection Due to Safe Uniform Load (in)  
C = Safe Concentrated Load (lbs/ft of grating width)  
D<sub>c</sub> = Deflection Due to Safe Concentrated Load (in)  
Allowable Extreme Fiber Stress = 20 ksi


Bearing Bar Size (inches)	Approx. Weight (lbs/ft <sup>2</sup> )	Ped. Span (inches)	Load / Deflection	Span (ft -in)												Section Properties			
				1' - 0"	1' - 6"	2' - 0"	2' - 6"	3' - 0"	3' - 6"	4' - 0"	4' - 6"	5' - 0"	5' - 6"	6' - 0"	6' - 6"	7' - 0"	7' - 6"	8' - 0"	S <sub>x</sub> (in <sup>3</sup> )/ft
1" x 1/4"	6.77	44	U D <sub>u</sub> C D <sub>c</sub>	2,000	889	500	320	222	163	125								0.150	
				0.03	0.06	0.11	0.17	0.25	0.34	0.44								0.056	
1 1/4" x 1/4"	8.13	55	U D <sub>u</sub> C D <sub>c</sub>	3,556	1,580	889	569	395	290	222	176	142						0.267	
				0.02	0.05	0.08	0.13	0.19	0.25	0.33	0.42	0.52						0.133	
1 1/2" x 1/4"	9.49	65	U D <sub>u</sub> C D <sub>c</sub>	5,556	2,469	1,389	889	617	454	347	274	222	184					0.417	
				0.02	0.04	0.07	0.10	0.15	0.20	0.26	0.34	0.41	0.50					0.260	
1 1/2" x 3/8"	13.74	71	U D <sub>u</sub> C D <sub>c</sub>	8,333	3,704	2,083	1,333	926	680	521	412	333	275	231				0.625	
				0.02	0.04	0.07	0.10	0.15	0.20	0.26	0.34	0.41	0.50	0.60				0.391	
2" x 1/4"	12.21	83	U D <sub>u</sub> C D <sub>c</sub>	10,889	4,840	2,722	1,742	1,210	889	681	538	436	360	302	258	222		0.817	
				0.01	0.03	0.05	0.07	0.11	0.14	0.19	0.24	0.30	0.36	0.43	0.50	0.58		0.715	
2 1/2" x 1/4"	14.93	100	U D <sub>u</sub> C D <sub>c</sub>	18,000	8,000	4,500	2,880	2,000	1,469	1,125	889	720	595	500	426	367	320	281	1.350
				0.01	0.02	0.04	0.06	0.08	0.11	0.15	0.19	0.23	0.28	0.33	0.39	0.45	0.52	0.59	
3" x 1/4"	17.65	117	U D <sub>u</sub> C D <sub>c</sub>	26,889	11,951	6,722	4,302	2,988	2,195	1,681	1,328	1,076	889	747	636	549	478	420	2.017
				0.01	0.02	0.03	0.05	0.07	0.09	0.12	0.15	0.19	0.23	0.27	0.32	0.37	0.42	0.48	2.773
3" x 3/8"	25.98	129	U D <sub>u</sub> C D <sub>c</sub>	40,333	17,926	10,083	6,453	4,481	3,293	2,521	1,992	1,613	1,333	1,120	955	823	717	630	3.025
				0.01	0.02	0.03	0.05	0.07	0.09	0.12	0.15	0.19	0.23	0.27	0.32	0.37	0.42	0.48	4.159

Spans and loads in red exceed a deflection of 1/4" for uniform loads of 100 lbs./sq. ft. Experience has shown that 1/4" deflection is the maximum deflection to give pedestrian comfort, but can be exceeded for other types of loads at the discretion of the specifying professional.

30HW4 (in)										
# of Bars	2	3	4	5	6	7	8	9	10	11
1/4" Bars	2-1/8	4	5-7/8	7-3/4	9-5/8	11-1/2	13-3/8	15-1/4	17-1/8	19
3/8" Bars	2-1/4	4-1/8	6	7-7/8	9-3/4	11-5/8	13-3/8	15-1/4	17-1/8	19
# of Bars	12	13	14	15	16	17	18	19	20	21
1/4" Bars	20-7/8	22-3/4	24-5/8	26-1/2	28-3/8	30-1/4	32-1/8	34	35-7/8	37-3/4
3/8" Bars	21	22-7/8	24-3/4	26-5/8	28-1/2	30-3/8	32-1/4	34-1/8	36	37-7/8

## LOAD TABLES - WIDE-GAP

**Grating Type:** 30HW4  
**Design Code:** NAAMM MBG 534-19  
**Material:** ASTM A1011CS Grade 36  
**Surface:** Serrated



U = Safe Uniform Load (lbs/ft<sup>2</sup>)  
D<sub>u</sub> = Deflection Due to Safe Uniform Load (in)  
C = Safe Concentrated Load (lbs/ft of grating width)  
D<sub>c</sub> = Deflection Due to Safe Concentrated Load (in)  
Allowable Extreme Fiber Stress = 20 ksi

Bearing Bar Size (inches)	Approx. Weight (lbs/ft <sup>2</sup> )	Ped. Span (inches)	Load / Deflection	Span (ft -in)												Section Properties			
				1' - 0"	1' - 6"	2' - 0"	2' - 6"	3' - 0"	3' - 6"	4' - 0"	4' - 6"	5' - 0"	5' - 6"	6' - 0"	6' - 6"	7' - 0"	7' - 6"	8' - 0"	S <sub>x</sub> (in <sup>3</sup> )/ft
3 1/2" x 1/4"	20.37	132	U D <sub>u</sub> C D <sub>c</sub>	37,556	16,691	9,389	6,009	4,173	3,066	2,347	1,855	1,502	1,242	1,043	889	766	668	587	2.817
				0.01	0.01	0.03	0.04	0.06	0.08	0.10	0.13	0.16	0.19	0.23	0.27	0.31	0.36	0.41	
3 1/2" x 3/8"	30.61	146	U D <sub>u</sub> C D <sub>c</sub>	56,333	25,037	14,083	9,013	6,259	4,599	3,521	2,782	2,253	1,862	1,565	1,333	1,150	1,001	880	4.577
				0.01	0.01	0.03	0.04	0.06	0.08	0.10	0.13	0.16	0.19	0.23	0.27	0.31</			